

# FONTAINE IO-SLACK®

## 6000PML

## Standard/Moderate duty applications Adjustable plate mount

Standard/Moderate duty On highway only 50.000 lbs vertical load 150,000 lbs drawbar pull Approx top plate weight 220 lbs

## **Mounting Bracket**

#### **Fontaine PML Adjustable Plate Mount**

- Two-inch adjustment increments give you greater versatility for improved payload distribution
- Computer design technology cuts excess weight without sacrificing one pound of capacity
- New greaseless bracket liner gives you consistent lubrication, reduces wear (no metal-to-metal contact) and cuts maintenance costs
- Dual durometer two-piece bushing for improved shock absorption and better support
- Computer designed cast bracket for lighter weight and greater strength
- Brackets are welded to a 3/8" steel plate that has six bolt holes on each side

# **Top Plate**

#### Fontaine No-Slack® 6000 Series Stamped Steel

- No-Slack lock self-adjusts to accommodate kingpin wear
  - Switch from trailer to trailer hassle-free
  - Snug, secure connection
  - Reduces shock inputs into frame when braking/accelerating
  - Improves driver comfort
  - Reduces driver complaints
  - Extends service life of components
- Locking trigger helps minimize high-hitching
  - Reduces driver frustration
  - Reduces tractor, trailer and tire damage
  - The industries best defense against false coupling
  - Saves expensive wrecker and clean up bills
- Easy coupling force—only 30 lbs!
  - Less wear and tear on the kingpin
  - Extends service life of drivetrain components
- Pull handle is the easiest to operate in the industry
  - Opens easily with a simple, straight pull of the handle
  - No complicated opening sequence to remember

### **Top Plate Performance Options**

- Retractable Pull Handle Handle retracts in the "open" position to help drivers avoid tire and fender damage.
- Air actuated— In-cab air release valve located on the dash opens the fifth wheel lock only when the tractor parking brakes are set.



www.fifthwheel.com • 800-874-9780 • Email: parts@fifthwheel.com

\* See your Fontaine Representative for application details or refer to Application Guide (LT-076) on website ©2019 Fontaine Fifth Wheel • LT-256 • March 2019 R2





