



FONTAINE NO-SLACK®

7000LWB

**Handles multiple applications
2-inch slide increments**

Standard/Moderate duty
On/Off highway
55,000 lbs vertical load
150,000 lbs drawbar pull
Approx top plate weight 245 lbs

Mounting Bracket

Fontaine LWB Light Weight Air Slide Bracket

- **Innovative weight saving design is lighter than its predecessor without losing an ounce of capacity— Save 20 to 50 lbs depending on configuration**
- **Computer-aided design features a smaller footprint with steel reinforcement for strength and durability**
- **New greaseless bracket liner provides consistent lubrication, reduces wear (no metal-to-metal contact) and cuts maintenance costs**
- **Two-inch slide increments give you greater versatility for improved payload distribution**
- **Quad-Lock four-point locking system increases locking surface area for greater stability and improved wear characteristics**
- **Automatically removes slack from the slide assembly for a smoother ride and longer life**
- **Dual durometer two-piece bushing for improved shock absorption and easier maintenance**

Top Plate

Fontaine No-Slack® 7000 Series Cast Steel

- **No-Slack lock self-adjusts to accommodate kingpin wear**
 - Switch from trailer to trailer hassle-free
 - Snug, secure connection
 - Reduces shock inputs into frame when braking/accelerating
 - Improves driver comfort
 - Reduces driver complaints
 - Extends service life of components
- **Locking trigger helps minimize high-hitching**
 - Reduces driver frustration
 - Reduces tractor, trailer and tire damage
 - The industries best defense against false coupling
 - Saves expensive wrecker and clean up bills
- **Easy coupling force—only 30 lbs!**
 - Less wear and tear on the kingpin
 - Extends service life of drivetrain components
- **Pull handle is the easiest to operate in the industry**
 - Opens easily with a simple, straight pull of the handle
 - No complicated opening sequence to remember

Top Plate Performance Options

- **Air actuated**— In-cab air release valve located on the dash opens the fifth wheel lock only when the tractor parking brakes are set.
- **Clean Connect™**— Special insert pads act as a lubricant between the top plate surface and the trailer coupling plate without grease. Improves steering, reduces steer tire wear and lowers operating cost since grease and labor to apply grease at every couple are no longer necessary.
- **LST Lock Sensing Technology**— Electronic sensors let the driver know that the kingpin is correctly positioned inside the lock and that the fifth wheel is closed. When the sensors indicate a successful coupling, a green light illuminates. After coupling, the system continuously monitors the connection and warns the driver with a red light if a change occurs.



www.fifthwheel.com • 800-874-9780 • Email: parts@fifthwheel.com

* See your Fontaine Representative for application details or refer to Application Guide (LT-076) on website

©2020 Fontaine Fifth Wheel • LT-252 • October 2020 R3



A Marmon |
Berkshire Hathaway
Company

Get the app @ FifthWheel.com/app

FontaineFifthWheel

@FifthWheelParts

